



Z-Trans 6P (GL)

Thermal Transfer Material

Description:

Z-Trans 6P (GL), an ultra smooth coated white paper label stock, produces excellent quality images, especially rotated bar codes, graphics and small characters, at print speeds up to 203.2mm per second. Compatible with Zebra 2100, 5518, 2300, 5049 and 5319 ribbons for standard thermal transfer printing. Suitable for use with Zebra 3200 ribbon for applications requiring improved smear and scratch resistance.

Suggested Applications

- Labelling of packaging materials.
- Cold temperature storage labelling.
- Compliance labelling.
- Product identification.
- Shipping labels.

Technical Specifications

Description		Caliper
Facestock	80gsm smooth white coated paper	80 microns
Adhesive	Permanent acrylic	20 microns
Liner	65gsm Glassine liner	60 microns
Total		160 microns

Recommended Zebra Ribbons: 2100, 2300, 5518, 5049, 5319, 3200, 5555, 3100, 5390, 5586

Minimum Application Temperature: -5°C (23°F)

Service Temperature Range: -20°C to 90°C (-4°F to 194°F)

Recommended Storage Conditions: One year duration when stored at 0°C to 21°C (32°F to 70°F) at 35% to 50% RH

Note: All products should be pre-tested to ensure that they meet all intended requirements of specific end-use applications. For testing of this material, please order **SAM5257**.

